

Model: STRIPE MATIKA SILVER 31,6X90(A) Codes: 100299437 Water absorption: BIII - Revestimiento (10%<=E<=20%)





DIMENSIONAL FEATURES UNE-EN ISO 10545-2				
Thickness	10.5 MM	+/-5%*		
Width	316 MM			
Length	900 MM			
Length and width deviation	Below 0.15%	+/-0.3%*		
Side straightness deviation	Below 0.15%	+/-0.3%*		
Squareness deviation	Below 0.15%	+/-0.3%*		
Surface flatness deviation	Below 0.15%	+/-0.4%*		
*ISO-13006:2018 UNE-EN 14411:2016				
MECHANICAL FEATURES UNE-EN ISO 10545-4-6-7-11				
Breaking strength	>1100 N	>600N*		
Modulus of rupture	>23 N/MM2	>=12N/mm2*		

*ISO-13006:20	018 UNE	-EN 144	11:2016

Crazing resistance

	HYGIENIC FEATURES UNE-EN ISO 10545-13-14:1995	
Chemical resistance	Class "A" for swimming pools and cleaning products (resists attack). Minimum Class "B" for acids and bases	B Min.*
Stain resistance *ISO-13006:2018 UNE-EN 14411:2016	Class 5. Easy cleaning with water	3 Min.*
	SCOPF OF USF	

Resists 3 cycles

Technical code-1	Use on walls	
	PACKING	
Sales units per box	1.137592 M2/BOX	
Sales units per pallet	58.017178 M2/PAL	
Sales units per unit	0.284398 M2/PIECE	



Do not use cleaning agents containing hydrofluoric acid. It is recommended to fix tiles with a minimum joint of 1,5 mm. Do not fix without joint. For big sizes, it is recomended to fix with mortars containing polymeric additives and to use the double glueing technique. Mosaic tiles must be grouted. This document is only commercial and cannot be used as expert opinion, documentary evidence or in any legal or administrative procedure unless authorized by PORCELANOSA S.A.