

Model: LUCERNA ACERO 45X120(A)

Codes: 100319138

Water absorption: BIII - Revestimiento (10%≤E≤20%)



DIMENSIONAL FEATURES

 UNE-EN ISO 10545-2

| | | |
|-----------------------------|-------------|----------|
| Thickness | 10 MM | +/-5%* |
| Width | 450 MM | |
| Length | 1200 MM | |
| Length and width deviation | Below 0.15% | +/-0.3%* |
| Side straightness deviation | Below 0.15% | +/-0.3%* |
| Squareness deviation | Below 0.15% | +/-0.3%* |
| Surface flatness deviation | Below 0.15% | +/-0.4%* |

*ISO-13006:2018 UNE-EN 14411:2016

MECHANICAL FEATURES

 UNE-EN ISO 10545-4-6-7-11

| | | |
|--------------------|------------------|------------|
| Breaking strength | >1100 | >600N* |
| Modulus of rupture | >23 | >=12N/mm2* |
| Crazing resistance | Resists 3 cycles | |

*ISO-13006:2018 UNE-EN 14411:2016

HYGIENIC FEATURES

 UNE-EN ISO 10545-13-14:1995

| | | |
|---------------------|--|---------|
| Chemical resistance | Class "A" for swimming pools and cleaning products (resists attack). Minimum Class "B" for acids and bases | B Min.* |
| Stain resistance | Class 5. Easy cleaning with water | 3 Min.* |

*ISO-13006:2018 UNE-EN 14411:2016

SCOPE OF USE

| | | |
|------------------|--------------|--|
| Technical code-1 | Use on walls | |
|------------------|--------------|--|

PACKING

| | | |
|------------------------|-------------------|--|
| Sales units per box | 1.619958 M2/BOX | |
| Sales units per pallet | 64.798315 M2/PAL | |
| Sales units per unit | 0.539986 M2/PIECE | |

System Certification

