

Model: CORE WHITE NATURE L 59,6X59,6(A)

Codes: 100325520

Water absorption: Bla - Porcelanico (E<=0.1%)





| DIMENSIONAL FEATURES UNE-EN ISO 10545-2 | | | |
|--|-------------|----------|--|
| Thickness | 8.5 MM | +/-5%* | |
| Width | 596 MM | | |
| Length | 596 MM | | |
| Length and width deviation | Below 0.15% | +/-0.3%* | |
| Side straightness deviation | Below 0.15% | +/-0.3%* | |
| Squareness deviation | Below 0.15% | +/-0.3%* | |
| Surface flatness deviation | Below 0.15% | +/-0.4%* | |

^{*}ISO-13006:2018 UNE-EN 14411:2016

| MECHANICAL FEATURES | |
|---------------------------|--|
| UNE-EN ISO 10545-4-6-7-11 | |
| | |
| | |

Breaking strength Modulus of rupture 54.8 N/MM2 >=35N/mm2* Crazing resistance Resists 3 cycles

*ISO-13006:2018 UNE-EN 14411:2016

HYGIENIC FEATURES UNE-EN ISO 10545-13-14:1995

Chemical resistance Class "A" for swimming pools and cleaning products (resists attack). Minimum Class "B" for acids and bases Class 5. Easy cleaning with water 3 Min.* Stain resistance

*ISO-13006:2018 UNE-EN 14411:2016

SCOPE OF USE

Use on heavy traffic floors Technical code-1

ANTI-SLIP VALUE EN 16165: 2022 / ASTM C1028

Dynamic coefficient of friction 0.65 CI 1 Slip resistance (pendulum-wet)

*ISO-13006:2018 LINE-EN 14411:2016

| | PACKING | |
|------------------------|-------------------|--|
| Sales units per box | 1.776073 M2/BOX | |
| Sales units per pallet | 56.834328 M2/PAL | |
| Sales units per unit | 0.355215 M2/PIECE | |

System Certification





