

Model: GLEM WHITE POL.PV6 120X120(A)

Codes: 100331078

Absorption: Bla - Porcelanico (E<=0.1%)





		IAL FEATURES ISO 10545-2	
Length	1200 MM		
Thickness	6 MM		
Width	1200 MM		
Length and width deviation	Below 0.15%	+/-0.3%*	
Side straightness deviation	Below 0.15%	+/-0.3%*	
Squareness deviation	Below 0.15%	+/-0.3%*	
Surface flatness deviation	Below 0.15%	+/-0.4%*	

^{*}ISO-13006:2015 UNE-EN 14411:2017

MECHANICA	L FEATURES
UNE-EN ISO 10)545-4-6-7-11

1118.5 N Breaking strenght Modulus of rupture 43.6 N/MM2 RESISTE 3 CICLOS Crack resistance

*ISO-13006:2015 UNE-EN 14411:2017

HYGIENIC FEATURES UNE-EN ISO 10545-13-14

Chemical resistance MÍNIMO CLASE B Stain resistance CLASE 5

*ISO-13006:2015 UNE-EN 14411:2017

ANTI-SLIP VALUE CEN/TS 41901/02, DIN-51130 y ASTM A137.1

Dynamic coefficient of friction 0.34 CLO Slip resistance (pendulum-wet) >40** Slip resistance (pendulum-dry)

*ISO-13006:2015 UNE-EN 14411:2017

S	\sim)	П		0		П	2	7
_			-	_		_		_	н

Technical code-1 Use on medium traffic floors Technical code-2 No additional requirements

System Certification









100331078 GLEM WHITE POLISHED



	PACKING
Sales units per box	2.880184 M2/BOX
Sales units per pallet	80.645161 M2/PAL
Sales units per unit	1.440092 M2/PIECE

System Certification





