

Model: LIEM DARK POL.PV6 120X120(A)

Codes: 100331100

Absorption: Bla - Porcelanico (E<=0.1%)





DIMENSIONAL FEATURES  UNE-EN ISO 10545-2				
Length	1200 MM			
Thickness	6 MM			
Width	1200 MM			
Length and width deviation	Below 0.15%	+/-0.3%*		
Side straightness deviation	Below 0.15%	+/-0.3%*		
Squareness deviation	Below 0.15%	+/-0.3%*		
Surface flatness deviation	Below 0.15%	+/-0.4%*		

<sup>\*</sup>ISO-13006:2015 UNE-EN 14411:2017

MECHANICAL FEATURES
UNE-EN ISO 10545-4-6-7-11

1118.5 N Breaking strenght 43.6 N/MM2 Modulus of rupture RESISTE 3 CICLOS Crack resistance

\*ISO-13006:2015 UNE-EN 14411:2017

## **HYGIENIC FEATURES** UNE-EN ISO 10545-13-14

Chemical resistance MÍNIMO CLASE B Stain resistance CLASE 5

\*ISO-13006:2015 UNE-EN 14411:2017

ANTI-SLIP	VALUE

CEN/TS 41901/02, DIN-51130 y ASTM A137.1 CLO Slip resistance (pendulum-wet) Slip resistance (pendulum-dry) >40\*\*

\*ISO-13006:2015 UNE-EN 14411:2017

## **SCOPE OF USE**

Technical code-1 Use on medium traffic floors Technical code-2 No additional requirements

PACKING		
Sales units per box	2.880184 M2/BOX	
Sales units per pallet	80.645161 M2/PAL	
Sales units per unit	1.440092 M2/PIECE	

System Certification





