

Model: TAJ MAHAL SILK PV6 120X120(A)

Codes: 100331113

Absorption: Bla - Porcelanico (E<=0.1%)





DIMENSIONAL FEATURES UNE-EN ISO 10545-2				
Length	1200 MM			
Thickness	6 MM			
Width	1200 MM			
Length and width deviation	Below 0.15%	+/-0.3%*		
Side straightness deviation	Below 0.15%	+/-0.3%*		
Squareness deviation	Below 0.15%	+/-0.3%*		
Surface flatness deviation	Below 0.15%	+/-0.4%*		

^{*}ISO-13006:2015 UNE-EN 14411:2017

MECHANICAL FEATURES
UNE-EN ISO 10545-4-6-7-11

Breaking strenght 1118.5 N 43.6 N/MM2 Modulus of rupture RESISTE 3 CICLOS Crack resistance

HYGIENIC	FEATURES
UNF-FN ISO	10545-13-14

	577E E17 100 100 10 17	
Chemical resistance	MÍNIMO CLASE B	
Stain resistance	CLASE 5	
Resistance to thermal shock	RESISTE	

^{*}ISO-13006:2015 UNE-EN 14411:2017

	ANTI-SLIP VALUE CEN/TS 41901/02, DIN-51130 y ASTM A137.1	
Slip resistance (pendulum-wet)	CLO	
Slip resistance (pendulum-dry)	>40**	

^{*}ISO-13006:2015 UNE-EN 14411:2017

SCOPE OF USE		
Technical code-1	Use on medium traffic floors	
Technical code-2	No additional requirements	

System Certification







100331113 TAJ MAHAL SILK



PACKING		
Sales units per box	2.880184 M2/BOX	
Sales units per pallet	80.645161 M2/PAL	
Sales units per unit	1.440092 M2/PIECE	

System Certification





