

Model: TERRA MATT 33,3X100(A) Codes: 100338603

10	15					X	1
		at a subsection design.	or a distance of the second	and shirts and	and the second lines	and it was not a series	and the state of the
		M					
				N1	10	X	
			XI		A	X	XIN
		XI					
		XI	X	XI		MA.	
	XI		XIS		XI	Y	YIN
		X					
	XI	XI	VI.				1
							XIS
	XIN	(X)	1	X		()	N N
1							



	DIMENSIONAL FEATURES UNE-EN ISO 10545-2		
Length and width deviation	Below 0.15%	+/-0.3%*	
Side straightness deviation	Below 0.15%	+/-0.3%*	
Squareness deviation	Below 0.15%	+/-0.3%*	
Surface flatness deviation	Below 0.15%	+/-0.4%*	
*ISO-13006:2018 UNE-EN 14411:2016			
	MECHANICAL FEATURES UNE-EN ISO 10545-4-6-7-11		
Crazing resistance	Resists 3 cycles		
*ISO-13006:2018 UNE-EN 14411:2016			
	HYGIENIC FEATURES UNE-EN ISO 10545-13-14:1995		
Chemical resistance	Class "A" for swimming pools and cleaning products (resists attack). Minimum Class "B" for acids and bases	B Min.* s	
Stain resistance	Class 5. Easy cleaning with water	3 Min.*	
*ISO-13006:2018 UNE-EN 14411:2016			
	PACKING		

Sales units per box	1.332001 M2/BOX	
Sales units per pallet	58.608059 M2/PAL	
Sales units per unit	0.333 M2/PIECE	



Do not use cleaning agents containing hydrofluoric acid. It is recommended to fix tiles with a minimum joint of 1,5 mm. Do not fix without joint. For big sizes, it is recomended to fix with mortars containing polymeric additives and to use the double glueing technique. Mosaic tiles must be grouted. This document is only commercial and cannot be used as expert opinion, documentary evidence or in any legal or administrative procedure unless authorized by PORCELANOSA S.A.