

Model: LIEM GREY NAT.(6) 59,6X120(A) Codes: 100338765





| | DIMENSIONAL FEATU UNE-EN ISO 10545-2 | IRES | |
|---|---|----------|--|
| Length and width deviation | Below 0.15% | +/-0.3%* | |
| Side straightness deviation | Below 0.15% | +/-0.3%* | |
| Squareness deviation | Below 0.15% | +/-0.3%* | |
| Surface flatness deviation | Below 0.15% | +/-0.4%* | |
| *ISO-13006:2015 UNE-EN 14411:2017 | | | |
| | SCOPE OF USE | | |
| Technical code-1 | Use on medium traffic floors | | |
| | DACKINC | | |
| | PACKING | | |
| | | | |
| Sales units per box | 2.145616 M2/BOX | | |
| Sales units per box Sales units per pallet | 2.145616 M2/BOX 64.368474 M2/PAL | | |



Do not use cleaning agents containing hydrofluoric acid. It is recommended to fix tiles with a minimum joint of 1,5 mm. Do not fix without joint. For big sizes, it is recomended to fix with mortars containing polymeric additives and to use the double glueing technique. Mosaic tiles must be grouted. This document is only commercial and cannot be used as expert opinion, documentary evidence or in any legal or administrative procedure unless authorized by PORCELANOSA S.A.