

Model: ARS BEIGE POL.PV6 120X120(A) Codes: 100339674 Absorption: Bla - Porcelanico (E<=0.1%)



Sistema DAPc[®] Declaración Ambiental de Productor de Construcción

DIMENSIONAL FEATURES UNE-EN ISO 10545-2				
Length	1200 MM			
Thickness	6 MM			
Width	1200 MM			
Length and width deviation	Below 0.15%	+/-0.3%*		
Side straightness deviation	Below 0.15%	+/-0.3%*		
Squareness deviation	Below 0.15%	+/-0.3%*		
Surface flatness deviation	Below 0.15%	+/-0.4%*		
*ISO-13006:2015 UNE-EN 14411:2017				

	MECHANICAL FEATURES UNE-EN ISO 10545-4-6-7-11	
Breaking strenght	1118.5 N	
Modulus of rupture	43.6 N/MM2	
Crack resistance	RESISTE 3 CICLOS	
*ISO-13006:2015 UNE-EN 14411:2017		
	HYGIENIC FEATURES UNE-EN ISO 10545-13-14	
Chemical resistance	MINIMO CLASE B	
Stain resistance	CLASE 5	

*ISO-13006:2015 UNE-EN 14411:2017	
	ANTI-SLIP VALUE CEN/TS 41901/02, DIN-51130 y ASTM A137.1
Slip resistance (pendulum-wet)	CLO
Slip resistance (pendulum-dry)	>40**
*ISO-13006:2015 UNE-EN 14411:2017	

Technical code-1

Resistance to thermal shock

SCOPE OF USE

Use on medium traffic floors Technical code-2 No additional requirements

RESISTE



100339674 ARS BEIGE POLISHED

PORCELANOSA Grupo

	PACKING	
Sales units per box	2.880184 M2/BOX	
Sales units per pallet	80.645161 M2/PAL	
Sales units per unit	1.440092 M2/PIECE	



Do not use cleaning agents containing hydrofluoric acid. It is recommended to fix tiles with a minimum joint of 1,5 mm. Do not fix without joint. For big sizes, it is recomended to fix with mortars containing polymeric additives and to use the double glueing technique. Mosaic tiles must be grouted. This document is only commercial and cannot be used as expert opinion, documentary evidence or in any legal or administrative procedure unless authorized by PORCELANOSA S.A.