

Model: INVISIBLE WHITE NATURE 160X320(6)(A)

Codes: 100340672

Absorption: Bla - Porcelanico (E<=0.1%)

Family: INVISIBLE

Tone variations: V3



DIMENSIONAL FEATURES

UNE-EN ISO 10545-2

| | | |
|-----------------------------|-------------|----------|
| Length | 3200 MM | |
| Thickness | 6 MM | |
| Width | 1600 MM | |
| Length and width deviation | Below 0.20% | +/-0.3%* |
| Side straightness deviation | Below 0.15% | +/-0.3%* |
| Squareness deviation | Below 0.20% | +/-0.3%* |
| Surface flatness deviation | Below 0.20% | +/-0.4%* |

*ISO-13006:2015 UNE-EN 14411:2017

MECHANICAL FEATURES

UNE-EN ISO 10545-4-6-7-11

| | | |
|---------------------|------------|--|
| Breaking strenght | >1100 N | |
| Modulus of rupture | > 45 N/MM2 | |
| Abrasion resistance | <140 | |

*ISO-13006:2015 UNE-EN 14411:2017

HYGIENIC FEATURES

UNE-EN ISO 10545-13-14

| | | |
|---------------------|-------|--|
| Chemical resistance | MIN B | |
| Stain resistance | 5 | |
| Flammability | A1 | |

*ISO-13006:2015 UNE-EN 14411:2017

ANTI-SLIP VALUE

CEN/TS 41901/02, DIN-51130 y ASTM A137.1

| | | |
|--------------------------------|-----|--|
| Slip resistance (pendulum-wet) | CL1 | |
| Slip resistance (pendulum-dry) | >40 | |

*ISO-13006:2015 UNE-EN 14411:2017

ADDITIONAL NOTES

*CONTINUOUS COMPOSITION, MAXIMUM IMAGE DEVIATION 3CM (Avoid direct access from the outside if no abrasive protection device is provided)

PACKING

| | | |
|------------------------|---------------|--|
| Sales units per box | 5.12 M2/BOX | |
| Sales units per pallet | 215.04 M2/PAL | |
| Sales units per unit | 5.12 M2/PIECE | |

Certified company



Do not use cleaning agents containing hydrofluoric acid.

It is recommended to fix tiles with a minimum joint of 1,5 mm. Do not fix without joint.

For big sizes, it is recommended to fix with mortars containing polymeric additives and to use the double glueing technique.

Mosaic tiles must be grouted.

This document is only commercial and cannot be used as expert opinion, documentary evidence or in any legal or administrative procedure unless authorized by URBATEK S.A.

In its polished finish, due to high gloss, light reflection can create optical effects that resemble stains. In no case they do not comply with the ISO 13006 product standard.

Being the ceramic material that most resembles natural stone, it can show slight variations in shade, color spots and vein among pieces.

#Refer to section 4 of the support document DB/SUA 3. This material can be installed in public, dry areas with a slope under 6% (it gets the same classification as a Class 1 according to wet pendulum).

SCOPE OF USE

| | |
|------------------|--|
| Technical code-1 | 4 - Light Transit with Direct Access to the Outdoors |
| Technical code-2 | 1 - Dry interior floors |

RECOMMENDED USE LOCATIONS

Single-family dwelling

- Outdoor Premises: Porches, verandah, terrace, outdoor access or circulation area
- Indoor Premises - Dry: Entrance and other enclosures with direct opening to the outside (garden, terrace, storage room).
- Indoor Premises - Dry: Individual staircase
- Indoor Premises - Wet: Kitchen, mini kitchen in living area, laundry room
- Indoor Premises - Humid: Bathroom or Toilet

Collective housing

- Outdoor premises: Balconies, terraces, galleries (not accessible from the outside)
- Indoor Premises - Common Elements: Stairs and corridors with or without lifts
- Indoor Premises - Common Elements: Meter centralisation room
- Indoor Premises - Common Elements: Storage rooms for children's cars, bicycles, etc.
- Indoor Premises - Dwelling - Damp: Kitchen, mini kitchen and living area, laundry room
- Indoor Premises - Dwelling - Damp: Bathrooms or shower rooms

Public Residential

- Single or double rooms
- Group rooms
- Intensive use dormitories in residences, schools, etc.

Administrative

- Office with workstation
- Collective office, open plan office
- Meeting/conference room, shops and retail (sales area)

Commercial

- Shops and retail trade (Sales area)

Teacher

- Pre-school and Primary: Classroom without direct opening to the exterior
- Infant and Primary: Playroom, exercise, multi-purpose room without direct opening to the outside.
- Secondary, Baccalaureate and University: Other laboratories (physics, electricity, radiation, mechanics).

Sanitary

- Single-user room, isolation room
- Collective room
- Major and minor operating theatres. Operating theatres
- Radiological premises
- Rehabilitation, massage, therapy and rehabilitation centres
- Laboratories (no public access)

Public attendance

- Catering: Dining room, company cafeteria
- Libraries and reading rooms: Libraries, reading rooms, houses of worship, museums (Internal use)

Service, facilities

- Toilets in office areas, restricted use
- Sanitary premises special hygiene (hospitals, food)
- Premises for telephone, computer and other dry installations

Certified company



Do not use cleaning agents containing hydrofluoric acid.

It is recommended to fix tiles with a minimum joint of 1,5 mm. Do not fix without joint.

For big sizes, it is recommended to fix with mortars containing polymeric additives and to use the double glueing technique.

Mosaic tiles must be grouted.

This document is only commercial and cannot be used as expert opinion, documentary evidence or in any legal or administrative procedure unless authorized by URBATEK S.A.

In its polished finish, due to high gloss, light reflection can create optical effects that resemble stains. In no case they do not comply with the ISO 13006 product standard.

Being the ceramic material that most resembles natural stone, it can show slight variations in shade, color spots and vein among pieces.

#Refer to section 4 of the support document DB/SUA 3. This material can be installed in public, dry areas with a slope under 6% (it gets the same classification as a Class 1 according to wet pendulum).